

BAYMONT, INC.
30 RED BAY ROAD - P.O. BOX 18, GOLDEN, MS 38847
PRODUCTION PHONE: 877-454-8827
SALES PHONE: 662-454-7993
FAX: 662-454-9850

FIBERGLASS TUB/SHOWER BATH UNIT

INSTALLATION AND CLEANUP INSTRUCTIONS

The instructions as outlined below are to be followed in the installation of our units.

1. The unit should be examined for damage in shipping
2. Make sure the unit is as ordered (color, right or left hand, etc.)
3. Accurate measurements are obtained by using the TOP of the unit for overall dimensions.
4. Double check framed opening for size and insure the framing is plumb and square.
5. Lay out the location of the holes required for supply and mixing valves on the back of the unit. Drill 1/4" (or less) pilot holes from the front or back at marked locations. Cut holes to required size from the FINISHED side. A hole saw or flat wood spade bit of the correct size will give good clean holes. Bits should be 1/8" larger than the item to be inserted.
6. Install an approved drain, applying a non-hardening sealant between the finished side of the unit and the flange side of the drain.
7. Carefully remove all shipping braces and place unit in framed opening. CAUTION, do not flex sidewalls as damage may occur to the radius. It may be necessary to level the unit by shimming or trimming the support legs and/or back of the unit.
8. Spot fasten the unit flanges while constantly insuring that the unit remains level and all side walls are plumb.
9. Screw in flange locks or nailing flanges must be inserted into a stud or backer board.
 - A. Along top flange fasteners to be placed maximum 24" O.C. Flange locks are permissible to be used.
 - B. Along side flange of tub, tub/shower, a minimum of four screws evenly spaced as possible, on the tub, a minimum of two screws evenly spaced as possible.
10. Local codes should be followed installing plumbing hardware.
11. In dry wall applications, the dry wall must be placed over the fastening flange. Fasten the dry wall and tub flange into studs and/or backing, mud, tape and finish. If plaster is to be used, the lath must be nailed over the fastening flange and finished plaster to head. The previous applies to residential housing. Manufactured housing may install on top of the dry wall.

CARE AND CLEANING INSTRUCTIONS

After installation, unit may be cleaned with a liquid detergent and warm water. Tar or paint may be removed by using turpentine, paint thinner or acetone. DO NOT under any circumstances use harsh chemicals or abrasive cleaners as the finish will be marred. CAUTION should always be exercised when using all solvents.

In the event the surface should become marred or dull, the finish may be restored by using an automotive white polishing compound applied with cheese cloth or other soft cloth. Rub vigorously and then wipe off all residue. Then use a good automotive wax to complete the refinish process.

LIMITED WARRANTY

BAYMONT, INC. warrants to the owners of its one piece seamless tub/shower unit manufactured of fiberglass reinforced polyester resin, that they will, free of any charge, at its option, repair or exchange any unit found to be defective in workmanship or material when inspected by an authorized representative of BAYMONT, INC., for a period of no more than one (1) year from date of installation of the unit by a builder or plumber. The exchange does not include any cost of removing, installation or reinstallation.

This warranty will be void if the unit has been moved from the place of initial installation and/or if the unit was not installed in compliance with the instructions supplied by the manufacturer. In addition, this warranty does not apply if the unit has been damaged by accident, misuse, damage by fire, flood or act of God.

The owner agrees by use of this unit that the responsibility or obligations of the manufacturer will not extend to contingent or indirect damage or injury which may result from any such use, that the obligations of the manufacturer are limited to those stated herein and that no other obligations or responsibilities expressed or implied are assumed by the manufacturer, BAYMONT, INC.

Modifications of any nature to this unit without prior written approval of the manufacturer will void this warranty in its entirety.